Due: April 20, 2020

The purpose of these exercises is that of learning to treat numerical data that have been generated in Monte Carlo or Molecular Dynamics simulations.

DATA SETS: Two data files are provided: data1.txt, data2.txt. On each line there are three numbers: the first number is the Monte Carlo time, the second number and third number correspond to measurements. U_1 and U_2 are the two quantities reported in data1.txt (second and third column, resp.) and U_3 and U_4 are the two quantities reported in data2.txt.

Data are thermalized: check by looking at $U_i(t)$ versus Monte Carlo time t.

1) Blocking analysis. First, compute the average and error on $\langle U_i \rangle$ neglecting correlations, i.e., assuming that data are independent.

Second, generate blocked data. If $U_i(t)$, t = 1,200000 are the original data define

$$U^{(1)}(t) = \frac{1}{2} [U_i(2t-1) + U_i(2t)]$$

$$U^{(k)}(t) = \frac{1}{2} [U_i^{(k-1)}(2t-1) + U_i^{(k-1)}(2t)]$$

Compute average and error (again, assuming that data are independent) on the blocked variables for increasing values of k till the error stabilizes.

Repeat the analysis for all four observables U_1, U_2, \ldots Show your results for the error in a graph (error versus k) and report in a table the best estimate of the error for each observable.

- 2) Autocorrelation analysis. Compute the autocorrelation function for the four observables and the corresponding integrated autocorrelation time (report τ_{int} in a table for each observable). Use the estimates of the autocorrelation times to estimate the error on the sample mean of U_i . Compare the results with those obtained in the blocking analysis (report the results for the error in the same table).
- 3) **Jackknife**. Generate blocked variables with blocks of length 2500. They can be considered as essentially independent (is this consistent with previous results?). Define (i = 2, 3, 4)

$$R_i = \frac{\langle U_i \rangle}{\langle U_1 \rangle}.$$

Compute R_i and its error using the jackknife method applied to the blocked variables. Compare the error with those obtained by using the independent-error formula and the worst-error formula (use the errors computed with the autocorrelation analysis). Present the three different estimates in a table.

Meet meeting for explanations and questions at https://meet.google.com/fgx-evds-mgc: Wed 04/08, 6pm; Thu 04/09, 6pm; Wed 04/15, 6pm

Instructions for the MEET meeting

- Connect a few minutes before the beginning and wait for permission;
- Connect with camera and microphone **OFF**;
- Write on the chat if you want to speak;
- When allowed to speak, turn microphone and camera ON; ask the question and turn the microphone OFF; turn the microphone on at the end of the answer, if needed. If you're happy with the answer, turn the camera off.