

Index

Note: Page numbers followed by “f” and “t” indicates figures and tables, respectively.

A

Absolute humidity, 658
Absolute pressure, 464–466,
471–472, 485
Absolute viscosity, 652
Ac carrier, 219–238
Acceleration measurement, 380,
385, 398–400, 403,
587–591, 599–632
Accuracy, 13–44
Active filter, 159–161
Active instruments, 13–44
Address bus, 289–314
Address decoding, 289–314
Aggregation of measurement
errors, 75–130
Air-vane meter, 493–530
Airy point, 642
Alarms, 315–346
Aliasing, 146, 150–153
Amplification, 1–12, 161–165
Amplitude modulation (am),
219–238
Analog instruments, 13–44
Analog meters, 239–288
Analog signal processing,
154–155
Aneroid gauge, 463–492
Angle block, 648
Angle measurement, 646–648
Angle-measuring spirit level,
646–647, 647f
Angular acceleration, 599–632
Angular velocity, 599–632
Annubar, 499, 504
Anti-ambiguity track,
599–632

Apex bridge-circuit balancing,
177–218
Apparent viscosity, 652
ASIC (Application specific
integrated circuit), 289–314

B

Balanced force (MEMS)
accelerometer, 565–598
Bandwidth, 148–149, 239–288
Baratron gauge, 463–492
Barometer, 484
Bath tub reliability curve,
315–346
Beam balance, 547–564
Bell prover, 526, 526f
Bell-shaped distribution, 75–130
Bellows, 464, 468, 469f, 480f,
481–482, 489
Bevel protractor, 646
Bias, 13–44
Bias error, 45–74
Bimetallic thermometer,
438–440, 446
Bimetallic thermostat, 407–462
Bin, 75–130
Bore micrometer, 639f, 640
Bourdon tube, 468–471,
475–476, 481–482, 488
Box cube, 635f, 640
Bridge circuits, 1–12, 178–197,
210
a.c., 191–197, 200–201, 204,
206, 210
balancing, 177–218
d.c., 198, 210
error analysis, 177–218

British Calibration Service
(BCS), 131–144
BS 5750, 131–144
Bubbler unit, 531–546
Bus network, 310
Butterworth filter, 168,
169f–170f

C

Calibrated tank, 521–522, 522f
Calibration, 16–17, 37–39,
45–74, 131–144, 301, 304,
446–453, 482–488,
520–527, 542–543,
560–563, 585–587, 591,
594–596, 619, 630
calibration chain, 131–144
calibration error, 45–74
calibration frequency,
131–144
documentation, 131–144
Caliper, 637–639
Calorimetric gas sensor, 667
Cantilever beam (MEMS)
accelerometer, 565–598
Capacitance measurement,
177–218
Capacitance moisture meter, 656
Capacitive coupling noise,
45–74
Capacitive sensors, 376–377,
401–402, 463–492,
531–546, 565–598
Capillary viscometer, 652–653
Case structure (Labview),
357–358
Catalytic bead gas sensor, 667

Catalytic gate FET gas sensor, 669
 Centrifugal micromanometer, 486, 486f
 Centrifugal tachometer, 599–632
 Chart recorder, 239–288
 Chi-squared distribution, 75–130
 Chi-squared test, 75–130
 Choice of instrument. *See* Instrument choice
 Clamp-on meter, 177–218, 239–288
 Coded disc shaft encoder. *See* Shaft encoders
 Coefficient of viscosity, 651
 Color change badge, 667
 Color temperature indicators, 442–443, 446, 455
 Common mode noise, 45–74
 Communications, 293, 305–312
 Compact prover, 524, 524f, 527
 Compensating leads, 407–462
 Compensating resistance, 45–74
 Computer data logging, 239–288
 Computing principles, 289–314
 Confidence level, 75–130
 Confidence tests, 271, 277–278
 Contention protocol, 310
 Continuous thermocouple, 407–462
 Control bus, 293, 295–297
 Conversion tables: imperial-SI units, 1–2, 4–11, 676–679
 Coriolis meter, 495–497, 517, 521
 Corner frequency, 157–159
 Correlation test, 239–288
 Counter-timer, 204–205, 204f, 208, 209f
 Crayon temperature indicators, 407–462
 Creep, 547–564
 Cross correlation ultrasonic flowmeter, 493–530
 Cross sensitivity, 565–598
 Cross talk sensor, 375–406
 Cumulative distribution function, 75–130
 Current loop transmission, 219–238, 289–314

Current measurement, 177–218
 Current to voltage conversion, 219–238
 Current transformer, 177–218
 Curve fitting, 239–288

D

Dall flow tube, 498–499, 499f, 503
 Damping ratio, 13–44, 239–288
 DAQ. *See* Data acquisition
 Data analysis, 75–130
 Data acquisition, 145–176, 347–374
 Data bin, 75–130
 Data bus, 293–294, 307
 Data logging, 239–288
 Data presentation, 239–288
 Dead space, 13–44
 Deadweight gauge, 13–44, 481–484, 483f
 Decibel (dB), 239–288
 Deflection instruments, 13–44
 Depth gauge, 642
 Design of instruments. *See* Instrument design
 Dial gauge, 642–643
 Diaphragm-type pressure transducer, 465–468, 465f, 474, 481–482, 489
 Digital caliper, 639
 Digital micrometer, 640
 Differential amplification, 163–164
 Differential pressure, 464–465, 471–472, 481–482
 Differential transformers
 linear, 565–598
 rotational, 599–632
 Digital filter, 165–170, 364–367
 Digital instruments, 13–44
 Digital meters, 199–203, 239–288
 Digital recorder, 239–288
 Digital (storage) oscilloscope, 239–288
 Digital thermometer, 375–462
 Digital voltmeter (DVM), 177–218, 239–288

Dimension measurement, 633–672
 Dimension measurement calibration, 643–645
 Diode temperature sensors, 407–462
 Dipstick, 531–546
 Discharge coefficient, 493–530
 Displacement measurement
 rotational, 599–632
 translational, 375–406, 585–586
 Display of signals, 239–288
 Distributed control system, 305
 Distributed sensors, 385, 390–391, 441, 454–455
 Doppler effect, 375–406, 493–530
 Draft gauge, 463–492
 Dew point meter, 659–660
 DVM. *See* Digital voltmeter
 Dynamic characteristics of instruments, 13–44, 239–288
 Dynamic viscosity, 651

E

Eddy current sensors, 375–406
 Electrical signals
 measurement, 45–74, 177–218, 239–288
 recording, 239–288
 Electrochemical potential noise, 45–74
 Electromagnetic balance, 547–564
 Electromagnetic flowmeter, 508–510, 509f, 518
 Electronic balance, 549–551, 551f, 555
 Electronic pressure gauge, 463–492
 Electronic spirit level, 647
 Electronic vacuum gauge, 463–492
 Electrostatic coupling noise, 45–74
 Embedded software, 299
 Emissivity, 407–462
 Encoders. *See* Shaft encoders

- Environmentally-induced errors, 45–74
- Equal-arm balance. *See* Beam balance
- Error frequency distribution, 75–130
- Errors in measurement systems, 45–74, 177–218
- Error in single measurement, 75–130
- Ethernet, 289–314
- Extension leads, 407–462
- F**
- Falling body viscometer, 653
- Farad, 177–218
- Fault detection, 301–302, 305
- Fiber optic principles, 219–238
- recorder, 239–288
- sensors, 375–406, 433, 441–442, 446, 455, 463–492, 617, 627, 627f
- signal transmission, 219–238
- Fiber optic pyrometer, 407–462
- Fieldbus, 289–314
- Fire detection/prevention, 424, 437–438
- First order type instruments, 13–44
- Fixed points (temperature measurement), 407–462
- Flatness measurement, 649
- Float and tape gauge, 531–546
- Float systems, 531–546
- Flow measurement, 289–314, 375–406, 493–530
- calibration, 493–530
- mass flow rate, 493–530
- volume flow rate, 289–314, 493–530
- Flow smoothing vane, 499–500
- Flow nozzle, 498–499, 499f, 503
- Flow restriction meter, 493–530
- Force measurement, 547–564
- calibration, 560–563
- Fortin barometer, 484
- Fotonic sensor, 375–406, 565–598
- Frequency distribution, 75–130
- Frequency measurement, 177–218
- Frequency modulation (FM), 219–238
- Function generation (Labview), 361–362
- G**
- Gas chromatography, 670
- Gas sensing and analysis, 383, 389, 665–670
- Gas sensor calibration, 670
- Gas thermometer, 407–462
- Gate-type meter, 493–530
- Gauge block, 640–642
- Gauge factor, 375–406
- Gauge pressure, 464–466, 468–479, 478f, 483–486, 485f, 488–490
- Gaussian distribution, 75–130
- Gaussian tables, 75–130
- Glass electrode, 663–664
- Gold–chromium wire pressure sensor, 479, 485
- Goodness of fit, 75–130
- Graded index (in fiber optic cable), 219–238
- Graphical data analysis, 75–130
- Graphical data presentation, 239–288
- Graphical programming (Labview), 351–353
- Gravimetric flow calibration, 525
- Gray code, 599–632
- Gyroscopes, 375–406, 614–617, 625–628
- H**
- Hall-effect sensors, 375–406
- HART, 289–314
- Hay’s bridge, 177–218
- Heat detection, 424–425
- Heat-sensitive cable, 407–462
- Height gauge, 642–643
- Helix meter, 508
- Henry, 177–218
- Hertz (Hz), 177–218
- High pass filter, 158–159
- Histogram, 75–130
- Hot-wire anemometer, 517
- Hot-film anemometer, 517
- Humidity calibration, 660–661
- Humidity measurement, 658–660
- Hydrostatic systems, 531–546
- Hygrometer, 659
- Hysteresis, 13–44
- I**
- IEC61158 fieldbus, 289–314
- IEC61508, 315–346
- IEEE488 bus, 289–314
- Imaging, 375–462
- Imperial-SI units conversion tables, 1–2, 4–11, 676–679
- Imperial units, 1–12
- Inaccuracy, 13–44
- Incremental shaft encoder, 599–632
- Indicating instruments, 13–44
- Inductance measurement, 177–218
- Induction tachometer, 599–632
- Inductive coupling noise, 45–74
- Inductive sensors, 375–406, 565–632
- Inductosyn, 565–632
- Inertial flow meter, 493–530
- Inertial navigation systems, 599–632
- Infrared gas sensor, 669
- Instrument choice, 1–12
- Instrument design, 1–12, 48, 51, 55–56
- Instrumentation amplifier, 165, 165f
- Instrumentation networks, 305–306
- Integrated circuit transistor sensors, 407–462
- Intelligent devices, 45–74, 289–314
- in acceleration measurement, 565–598
- in angular displacement measurement, 629
- in flow measurement, 289–314, 493–530

- Intelligent devices (*Continued*)
 - in force and mass measurement, 547–564
 - in level measurement, 531–546
 - in pressure measurement, 463–492
 - in temperature measurement, 443–444, 455
- Intelligent sensor. *See* Intelligent devices
- Interfacing, 295–297, 306–307
- Internal micrometer, 640
- International practical temperature scale (IPTS), 407–462
- Intrinsic safety, 315–346
- Ionization gauge, 478f, 479, 486
- ISO 9000, 135, 137–138, 140

- K**
- Kinematic viscosity, 651

- L**
- Labview, 347–374
- LAN. *See* Local area network
- Laser Doppler flowmeter, 375–406, 493–530
- laser interferometer, 565–598
- Law of intermediate metals, 407–462
- Law of intermediate temperatures, 407–462
- Least squares regression, 239–288
- Length bar, 640–642
- Level of significance, 75–130
- Level measurement, 13–44, 375–406, 531–546
 - calibration, 542–543
- Line-type heat detector, 407–462
- Linear variable differential transformer (LVDT), 565–598
- Linearity, 13–44
- Liquid electrolyte electrochemical cell, 667–668
- Liquid-in-glass thermometer, 13–44, 438, 439f, 450, 452, 455
- Lisajous patterns, 177–218
- Load cell, 547–564
- Local area network, 305–306, 308–311, 313
- Lock-in amplifier, 45–74
- Logic operations (Labview), 355–356
- Loops (Labview), 356–357
- Low pass filter, 155, 155f–156f, 158
- Low resolution nuclear magnetic resonance (NMR) moisture measurement, 656–657
- LVDT. *See* Linear variable differential transformer

- M**
- Magnetic flowmeter, 493–530
- Magnetic sensors, 375–406, 599–632
- Magnetostrictive tachometer, 599–632
- Manganin wire pressure sensor, 463–492
- Manometers, 471–473, 477–478, 481–482, 484, 486, 488
- Manufacturing tolerances, 75–130
- Mass flow meter, 493–530
- Mass flow rate. *See* Flow measurement
- Mass measurement, 548–555
 - calibration, 560–562
- Mass spectrometer, 669
- Maxwell bridge, 177–218
- McLeod gauge, 477–479, 478f, 485, 488–490
- Mean, 75–130
- Mean-time-between-failures, 315–346
- Mean-time-to-repair, 315–346
- Mean time to replace, 315–346
- Measurement disturbance, 45–74
- Measurement noise reduction, 45–74
- Measurement noise sources, 45–74
- Measurement system design, 1–12, 45–74
- Measurement uncertainty, 13–44
- Measuring units, 1–12, 676–679
- Median, 75–130
- MEMS devices, 398–401, 444–445, 466–467, 474–475, 475f, 498, 559–560, 589–590, 614, 619, 628, 660, 662
- Metal oxide gas sensor, 669
- Meters, 239–288
- Metric units, 1–12
- Microbend sensor, 463–492
- Micro-electro-mechanical-systems devices. *See* MEMS devices
- Micromanometer, 486
- Micrometers, 138, 139f, 639–640
- Microprocessor, 289–314
- Microsensors. *See* MEMS devices
- Modem, 309
- Modifying inputs. *See* Environmentally-induced errors
- Moisture calibration, 660–661
- Moisture measurement, 655–661
- Monomode cable (fiber optic), 219–238
- Moving coil meters, 177–218, 239–288
- Moving iron meters, 177–218, 239–288
- Multimeters, 177–218, 241, 243, 247–248, 248f
- Multimode cable (fiber optic), 219–238
- Multiple earths noise, 45–74
- Multiplexing, 225, 231
- Multivariable transmitter, 289–314
- Multiwavelength pyrometer, 407–462

- N**
- Nano-scale-electro-mechanical-system devices. *See* NEMS devices
- National Measurement Accreditation Service (NAMAS), 131–144

National Standards
 Organisations, 131–144
 National Testing Laboratory
 Accreditation Scemem
 (NATLAS), 131–144
 Natural frequency of instruments,
 13–44
 Neutron moderation moisture
 measurement, 656
 NEMS devices, 375–406
 Networks, 289–314
 Normal distribution, 75–130
 Normal probability plot, 75–130
 Nozzle flapper, 565–598
 Nuclear sensors, 375–406, 495
 Null type instruments, 13–44
 Numerically controlled machine
 tools, 576–577, 580, 604,
 610–611
 Nutating disk flowmeter, 507
 Nyquist frequency, 149–151,
 168–169
 Nyquist rate, 146, 150–151

O

Obstruction meter, 493–530
 Ohmmeter, 177–218
 One-out-of-two voting, 315–346
 Optical fibers. *See* Fiber optics
 Optical incremental shaft
 encoder, 599–632
 Optical pyrometer, 407–462
 Optical resonator, 375–406
 Optical pressure sensor, 463–492
 Optical sensors, 375–406
 Optical shaft encoder, 599–632
 Optical tachometer, 599–632
 Optical wireless telemetry,
 219–238
 Orifice plate, 498–500,
 499f–501f, 502, 518–519,
 525
 Oscilloscope, 206, 209–210,
 239–288
 Oval gear flowmeter, 507

P

Paperless recorder, 239–288
 Paper tape gas sensor, 667
 Parallax error, 239–288

Parallel databus (communication
 interface), 307–308
 Passive filter, 155–159
 Passive instruments, 13–44
 PCM. *See* Pulse code modulation
 pH measurement, 663–665
 calibration, 665
 Phase-locked loop, 45–74,
 177–218
 Phase measurement, 177–218
 Phase-sensitive detector,
 177–218
 Photon detector, 432–433, 435
 Piezoelectric transducers,
 375–406
 Piezoresistive transducers,
 375–406, 463–492
 Pipe prover, 522–523, 523f
 Pirani gauge, 463–492
 Piston gauge, 483–484
 Pitot tube, 499, 503–504
 Platinum resistance thermometer,
 407–462
 Pneumatic signal transmission,
 219–238
 Positive displacement flowmeter,
 524, 526
 Potentiometers, 13–44,
 565–598, 600, 601f, 618
 induction, 599–632
 rotational, 599–632
 translational, 565–598
 Precession, 599–632
 Precision, 13–44
 Precision error, 45–74
 Presentation of data. *See* Data
 presentation
 Pressure balance, 483–484
 Pressure measurement, 13–44,
 463–492
 calibration, 463–492
 high pressures, 463–492
 low pressures, 463–492
 Pressure thermometer, 440, 446,
 455
 Primary fixed point (of
 temperature), 407–462
 Primary reference standard,
 131–144
 Probability curve, 75–130

Probability density function,
 75–130
 Programmable transmitters, 303
 Programming and program
 execution, 289–314
 Proof ring, 549f, 562
 Protractor, 646, 646f
 Proximity sensors, 565–598
 PRT. *See* Platinum resistance
 thermometer
 Psychrometer, 659
 Pulse code modulation (PCM),
 219–238
 Pyrometers, 431–436, 441
 Pyrometric cone, 407–462

Q

Q factor (quality factor),
 177–218
 Quantization, 154, 348–349

R

Radiation pyrometer/
 thermometer. *See*
 Pyrometers
 Radio telemetry, 219–238
 Random access memory (RAM),
 289–314
 Random errors, 45–130
 Range (of instrument), 13–44
 Range measurement, 375–406,
 565–598
 Ratio pyrometer, 407–462
 Read only memory (ROM),
 289–314
 Recorders. *See* Signal recorders
 Redundancy, 315–346
 Reference plane, 635–636
 Reference standards, 131–144
 Refractive index measurement,
 375–406
 Refractometer, 657
 Regression techniques, 239–288
 Relative humidity, 659
 Reliability, 315–346
 components in parallel,
 315–346
 components in series, 315–346
 manufacturing systems,
 315–346

Reliability (*Continued*)
 measurement systems, 315–346
 safety systems, 315–346
 software, 315–346
 Repeatability/reproducibility, 13–44
 Resistance measurement, 178, 197–200
 Resistance temperature device (RTD), 425–427, 445, 451
 Resistance thermometer, 425–427, 445, 451
 Resistive sensors, 375–406
 Resolution, 13–44
 Resolver, 599–632
 Resonant-wire pressure sensor, 473–474, 481–482
 Reynolds number, 493–530
 Rice rule, 75–130
 Ring laser gyroscope, 599–632
 Ring network, 289–314
 Rise time, 239–288
 Risk analysis, 315–346
 Rogue data points, 75–130
 Rotameter, 493–530
 Rotary differential transformer, 599–632
 Rotary piston flowmeter, 493–530
 Rotational acceleration, 599–632
 Rotational displacement, 599–632
 Rotational velocity, 599–632
 Rotational viscometer, 653–654
 RS232 interface, 289–314
 RTD. *See* Resistance thermometer
 Rule, 636–637

S

Safety systems, 315–346
 safety integrity level (SIL), 315–346
 Sampling, 348–349
 SAW device. *See* Surface acoustic wave technology device
 Scale factor drift, 13–44
 Second order type instruments, 13–44, 239–288

Secondary fixed point (of temperature), 407–462
 Secondary reference standard, 131–144
 Seger cone, 407–462
 Selected waveband pyrometer, 407–462
 Selection of instruments. *See* Instrument choice
 Self-calibration, 301, 304
 Self-diagnosis, 301–302, 305
 Selsyn, 599–632
 Semiconductor gas sensor, 669
 Semiconductor strain gauge, 375–406
 Semiconductor temperature sensor, 429, 445, 454
 Sensitivity drift, 13–74
 Sensitivity of measurement, 26–27, 29–30
 Sensitivity to disturbance, 13–44
 Sensor, 1–12
 Serial mode noise, 45–74
 Setting gauge, 644
 Shaft encoders, 599–632
 Shielding, 45–74, 219–238
 Shock measurement, 594–596
 calibration, 595–596
 Shot noise, 45–74
 SI units, 1–12, 676–679
 Sigma-delta technique, 375–406
 Signal amplification, 161–165
 Signal display, 239–288
 Signal measurement, 239–288
 Signal processing, 1–12, 145–176
 Signal recording, 131–144, 239–288
 Signal sampling, 348–349
 Signal-to-noise ratio, 45–74
 Signal transmission, 1–12, 219–238, 289–314
 Sine bar, 647, 648f
 Sing-around flowmeter, 493–530
 Single mode cable (fiber optic), 226
 Slip gauge, 640–642
 Smart microsensor, 289–314
 Smart sensor, 290, 298–302, 304, 313

Smart transmitter, 290, 298–305, 313
 Smoke detector, 375–406
 Solid state electrochemical cell, 668
 Sound calibration, 662–663
 Sound measurement, 661–663
 Sound pressure level, 661
 Sources of measurement noise, 45–74
 Span, 13–44
 Specific humidity, 658
 Spring balance, 547–564
 Standard deviation, 75–130
 Standard error of the mean, 75–130
 Standard measurement units, 1–12, 676–679
 Standards Laboratories, 131–144
 Standby systems, 315–346
 Star network, 289–314
 Static characteristics of instruments, 13–44
 Static sensitivity of instruments, 13–44
 Statistical analysis of data, 75–130
 Step index (in fiber optic cable), 230–231
 Storage oscilloscope, 239–288
 Strain gauge, 381–383, 402, 463–492, 565–598
 Stroboscopic velocity measurement, 599–632
 Student *t*-distribution, 75–130
 Sturgis rule, 75–130
 Surface acoustic wave technology device, 547–564
 Surface plate, 635–636
 Synchro, 599–632
 Synchro-resolver, 599–632
 Synchro transformer/transmitter, 599–632
 Systematic errors, 45–74

T

Tabular data presentation, 239–288
 Tachometric generators (tachometers), 599–632

Tank gauge, 531–546
 Tape, 636–637
 Target meter, 493–530
 Telemetry, 219–238
 Temperature coefficient, 55–56,
 407–462, 565–598
 Temperature measurement, 377,
 388–390, 398–399,
 402–404, 407–462
 calibration, 407–462
 Thermal anemometry, 517
 Thermal detector, 407–462
 Thermal e.m.f., 45–74, 407–462
 Thermal imaging, 437–438
 Thermal mass flow meter,
 493–530
 Thermistor, 427–429, 445, 451
 Thermistor gauge, 463–492
 Thermocouple, 409–425, 427,
 444–445, 448
 Thermocouple gauge, 463–492
 Thermocouple tables, 407–462,
 687t
 Thermoelectric effect, 45–74,
 407–462
 Thermoelectric potential noise,
 45–74
 Thermography, 407–462
 Thermometer (liquid-in-glass
 type), 13–44, 438, 439f,
 450, 452, 455
 Thermopile, 407–462
 Thevenin's theorem, 13–18,
 45–74, 177–218
 Threshold, 13–44
 Time base circuit, 239–288
 Time constant, 13–44
 Tolerance, 13–74
 Tools palette (Labview),
 353–355
 Torque measurement, 547–564
 calibration, 560, 562–563
 Total measurement error, 75–130
 Touch screens, 260

Traceability, 131–144
 Transducer, 1–12
 Transmitter, 1–12
 Translational acceleration,
 587–591
 Translational displacement,
 585–586
 Translational velocity, 586–587
 Triggering, 239–288
 Tube viscometer, 652–653
 Turbine meters, 507–508, 525
 Two-color pyrometer, 407–462
 Two-out-of-three voting,
 315–346

U

UART interface, 289–314
 U-tube manometer, 471–472,
 472f, 484, 488
 Ultrasonic flowmeters, 511–516,
 518–519
 Ultrasonic imaging, 375–406
 Ultrasonic level gauge, 531–546
 Ultrasonic principles, 375–406
 Ultrasonic rule, 636–637, 644f
 Ultrasonic thermometer,
 407–462
 Ultrasonic transducers, 375–406
 Uncertainty, 13–44
 Units of measurement, 1–12,
 676–679
 USB (universal serial bus),
 289–314

V

Vacuum pressures, 475–479
 Variable area flowmeter,
 504–505, 505f, 520
 Variable reluctance sensors,
 375–406, 620–622, 622f
 Variance, 75–130
 gauge, 649
 Vee block, 635–636, 635f

Velocity measurement
 rotational, 599–632
 translational, 586–587
 Venturi, 498–500, 499f, 503
 Vernier caliper, 637–638, 638f
 Vibrating cylinder gauge, 485
 Vibrating level sensor, 531–546
 Vibrating wire force sensor,
 547–564
 Vibration measurement,
 591–593
 calibration, 594
 Virtual instrument, 350–351
 Viscosity calibration, 654
 Viscosity measurement, 651–654
 Voltage to current conversion,
 219–238
 Voltage to frequency conversion,
 219–238
 Voltage transient noise, 45–74
 Volume flow rate measurement.
 See Flow measurement
 Volume measurement, 649–651
 Vortex shedding flowmeter,
 510–511, 510f, 525

W

Weigh beam, 547–564
 Wein bridge, 177–218
 Wheatstone bridge, 177–218
 Wire pressure sensor, 463–492
 Woltmann meter, 508

X

χ^2 . *See* Chi-squared
 $X - Y$ plotter, 177–218

Z

z -distribution, 75–130
 Zero drift, 13–74
 Zero order type instruments,
 13–44
 Zirconia sensor, 668